```
SELECT *
FROM sailor S
WHERE S.age>15;

SELECT *
FROM sailor S
WHERE (S.age>15) AND (S.rating >9);

SELECT *
FROM sailor S
WHERE (S.age>15) AND (S.rating >9) OR (S.sid>13);

SELECT *
FROM sailor S
WHERE (S.age>15) AND ((S.rating >9) OR (S.sid>13));

SELECT *
FROM sailor S
WHERE S.rating=NULL;

SELECT *
FROM sailor S
WHERE S.rating IS NULL;

SELECT *
FROM sailor S
WHERE (S.rating IS NOT NULL) AND S.age > 15;

SELECT R.sid, R.bid, R.r_date
FROM reservation R
WHERE R.r_date >'01/30/2001';

SELECT R.sid, S.sname, R.bid, R.r_date
FROM reservation R, sailor S
WHERE R.sid=S.sid
AND R.r_date >'01/30/2001'

ALTER TABLE sailor ADD height real;

SELECT *
FROM sailor S
WHERE S.sname LIKE 'Θ%';


SELECT *
FROM sailor S
WHERE S.sname LIKE '__ρ%';
```

...επίσης: >1 λογισμικά/πελάτης που μπορούν να συνδεθούν στον εξυπηρετητή (db2 server)